



Celestial Star™ LED/Celestial Star™

The Celestial Star™ is ideal for surgical applications and procedures where maneuverability and compact design are key requirements. These areas include urgent care facilities, outpatient surgery centers and minor surgical applications. The light provides excellent illumination, and offers market leading reach and flexibility. In addition the Celestial Star™ minimizes shadows and incorporates a balance arm that provides drift free performance. Available in single & dual ceiling, wall, and mobile configurations.

Tri-Star™ LED / Tri-Star™

Excellent performance and great value is what the TriStar™ has to offer. Ideal for medical examinations and minor surgical patient procedures. The unique telescoping pole offers height adjustment in the mobile configuration and is one of the only products in the market with this functionality. The wall model offers extensive reach with a unique extension arm design.

“Ideal for surgical applications and procedures.”



Features:

- Unparalleled flexibility with extensive reach and range of motion
- Virtually maintenance free
- Drift free balance arm design
- 114-inch reach from head to toe
- Patented lamp shade reduces heat output
- (3) 35W long life Halogen bulbs (average over 4,000 hours)
- Removable, sterilizable handle
- Available in single & dual ceiling, wall, and mobile configurations



Features:

- Unique mobile stand, raises from 27 to 80 inches via one hand control for quick height adjustment
- Casters move easily across all surfaces; base design prevents tipping
- Wall model offers 30 inch extension arm, providing 55 inches of reach to beam center
- (3) 20W long life Halogen bulbs (average over 4,000 hours)
- Available in wall and mobile configurations



Celestial Star™




Sunnex • 8001 Tower Point Drive • Charlotte, NC 28227 • U.S.A. • Toll Free (800) 445-7869
Fax: (888) 668-1920 • Email: info@sunnex.com • Web Site: www.sunnex.com

Tri-Star™



Celestial Star™



Tri-Star™



TECHNICAL DATA

Feature	Celestial Star™ LED / Celestial Star™	Tri-Star™ LED / Tri-Star™
Power Supply	120V / 60 Hz AC -or- 230-240V / 50 Hz AC	120V / 60 Hz AC -or- 230-240V / 50 Hz AC
Light Intensity	Up to 6,000 Footcandles/64,000 Lux	Up to 4,000 Footcandles/38,000 Lux
Light Source	(3) Halogen bulbs – 3x35W	(3) Halogen bulbs – 3x20W
	(3) LED modules – 3x12W / 50,000-hour life	(3) LED modules – 3x12W / 50,000-hour life
Light color temperature	Halogen – Up to 3,000K	Halogen – Up to 4,100K
	LED - 4,000K	LED - 4,000K

Mount Options

Options	Celestial Star™ part no.		Tri-Star™ part no.	
	Halogen	LED	Halogen	LED
Ceiling	CS2050C	CSLED-C	-	-
Dual Ceiling	CS2050D	CSLED-D	-	-
Wall	CS2050W	CSLED-W	TS2035W	TSLED-W
Mobile	CS2050M	CSLED-M	TS2035M	TSLED-M
Extra Sterilizable Handle	18544	-	-	-
Color Corrective filter	18676	-	18676	-

Specifications

Model	Celestial Star™	Tri-Star™
Ceiling	52 lbs	-
Dual	104 lbs	-
Wall	54 lbs	27 lbs
Mobile	35 lbs	37 lbs